

PULSOR P2

CONSTRUCTION & MINING EQUIPMENT

Concrete pump and placement

For rotary concrete pumps in which the hose is compressed by the peristaltic pump rollers.

Advantages

- ▮ Excellent strength and flexibility due to the hose construction.
- ▮ A perfected steel-to-rubber bonding technique.
- ▮ Extremely efficient steel cord reinforcement.
- ▮ A tube highly resistant to the abrasive action of concrete.
- ▮ A full range of hose diameters for all types of rotary pumps.
- ▮ High fatigue life design

Technical description

Inner tube: wear resistant NR, black, smooth.

Reinforcement: steel cords.

Cover: NR, black, fabric impression.

Temperature range: -30°C to +80°C.


TRELLEBORG
PULSOR P2

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (l) or min. order m
75.0	15.75 ±1.00	106.5 ±1.5	40	200	0.8	500	17.76	2.87	0128965	223.85999
100.0	18.25 ±1.00	136.5 ±1.75	40	150	0.8	500	30.3	3.3	0125123	237.59999
								3.45	0128964	l
115.0	18.0 ±1.00	151.5 ±2.0	40	120	0.5	500	35.35	3.54	0129322	∞
125.0	21.25 ±1.00	167.5 ±2.0	40	120	0.8	600	50.35	3.85	0128963	l

∞ Upon availability.

Tolerance on length: ±1% (ISO 1307 Standard).

Branding



and embossed: week/year

Gomas
Dauper S.L.