

STEAM 18 RED

OIL & GAS

Especificaciones técnicas

Tubo interior : negro.

Revestimiento : rojo.

Temperadura : -30°C a +210°C.


 TRELLEBORG STEAM 18 RED - EN ISO 6134:2005 - 2A - STEAM - 18 BAR - 210°C - 38 - Ø - 1Q/16

Diam. int. mm		Diam. ext. mm		Presión de servicio bar	Presión de rotura bar	Radio de curvatura mm	Peso kg/m	Longitud m	Código artículo	Stock (l) o cant min m
13.0	±0.5	25.0	±1	18	180	130	0.52	40	5513659	l
16.0	±0.5	30.0	±1	18	180	160	0.77	40	5513660	l
19.0	±0.5	33.0	±1	18	180	190	0.89	40	5513661	l
25.0	±0.5	40.0	±1	18	180	250	1.11	40	5513662	l
32.0	±0.5	48.0	±1	18	180	320	1.44	40	5513663	l
38.0	±0.5	54.0	±1.2	18	180	380	1.75	40	5513664	l
51.0	±0.7	69.0	±1.4	18	180	500	2.31	40	5513665	l

Tolerancia sobre la longitud : +1% (norma ISO 1307).

Marcado


 TRELLEBORG STEAM 18 RED - EN ISO 6134:2005 - 2A - STEAM - 18 BAR - 210°C - 38 - Ø - 1Q/16

AUT VIAN INVENIAM AUT FACIAM

Gomas

Dauper S.L.